



PRODUCT SPECIFICATIONS DOMO Duraforce XSL 60M/16

Applications	Soccer
Fibre	100% Polyethylene X Soft / 100% Monofilament straight / Diamond Plus / 360 µm thickness / 13.500 dtex
Production Method	Linear tufting
Gauge	5/8"
# stitches / lm	160 / lm
# tufts / m ²	10.080 / m ²
# piles / m ²	120.960 / m ²
Pile Height	60 mm
Pile Weight	1.910 gr / m ²
Total Height	62 mm
Total Weight	3.162 gr / m ²
Tuft cloth	Polypropylene, UV-Stabilized, 252 gr / m ²
Backing	Latex, 1.000 gr / m ²
Infill	See laboratory test report
Shock pad	See laboratory test report
Roll Width	400 cm
Roll Length	As per lay-out
Colour	Green
Colour Lines	White / Yellow / Red / Blue
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	>5.000 hours UV-A
Water Permeability	6.10 ⁻⁴ m/s
Pile Enchorage	> 30 N

Sports and Leisure Group NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data (max.10%). Sports and Leisure Group NV guarantees the technical quality of the proposed article.



A POWERFUL EXPERIENCE