



## PRODUCT SPECIFICATIONS **DOMO Smash**

Applications	Tennis, Multisports
Fibre	Polypropylene / UV-stabilized / Straight / Fibrillated 6.600 dtex 12 mm ca. 60 micron
Production Method	Linear tufting
Gauge	5/16"
# stitches / lm	ca. 175 / lm
# tufts / m <sup>2</sup>	ca. 22.047 / m <sup>2</sup>
# piles / m <sup>2</sup>	ca. 44.094 / m <sup>2</sup>
Pile Height	ca. 22 mm
Pile Weight	ca. 770 gr / m <sup>2</sup>
Total Height	ca. 24 mm
Total Weight	ca. 1.804 gr / m <sup>2</sup>
Tuft Cloth	Polypropylene, UV-stabilized, ca. 134 gr / m <sup>2</sup>
Backing	Latex, ca. 900 gr / m <sup>2</sup>
Infill	Sand (ca. 24 kg)
Roll Width	370 or 400 cm
Roll Length	As per lay-out
Colour	Green / Red
Colour Lines	White / Yellow
Colour Fastness	Scale 7 (DIN 54004)
UV-Stability	> 6.000 hours (DIN 53387)
Water Permeability	6.10 <sup>-4</sup> m / sec
Inflammability	Class 1 (DIN 51960)
Pile Anchorage	> 30 N
Test Reports	ITB / AT-15-5743/2002 (Polish & English) ISA / ITF CS/01/01-05-091 (English)

DOMO Zele NV reserves the right to amend technical specifications on the above mentioned product. Delivered products can slightly differ from these technical data. DOMO Zele NV guarantees the technical quality of the proposed article.